



SPECIFICATIONS		
CHUCK TYPE	YAST -250S	
CYLINDER DIA	250 mm	
PISTON STROKE	60 mm	
PISTON AREA	EXTEND 481.5 cm <sup>2</sup>	RETRACT 450 cm <sup>2</sup>
MAX. DRAW BAR PULL	EXTEND 18,270 Kgf	RETRACT 17,078 Kgf
MAX. OPERATING PRESSURE	4.0 MPa (40.8 Kgf/cm <sup>2</sup> )	
MIN. OPERATING PRESSURE	0.5 MPa ( 5 Kgf/cm <sup>2</sup> )	
MAX. PERMISSIBLE SPEED	2000 rpm	
WEIGHT	Kg	
MOMENT OF INERTIA(GD <sup>2</sup> )	Kg .m <sup>2</sup>	
TATAL LEAKAGE	1.0 L/min	
( 1 KN = 100 kgf , 1 MPa = 10 kgf/cm <sup>2</sup> )		

SCALE	PROJECTION	ITEM NO.	YAST-250S
1:1		PART NAME	CLOSED HYDRAULIC SLIM CYLINDER CHECK VALVE+PROXIMITY SWITCH TYPE
		PART NO.	2AST25S
서암기계공업주식회사 SEOAM MACHINERY INDUSTRY CO., LTD.			