



SPECIFICATIONS

CHUCK TYPE	YASC - 125	
CYLINDER DIA	130 mm	
PISTON STROKE	25 mm	
PISTON AREA	EXTEND 132.5 cm <sup>2</sup>	RETRACT 123.0 cm <sup>2</sup>
MAX. DRAW BAR PULL	EXTEND 4,978 Kgf	RETRACT 4,621 Kgf
MAX. OPERATING PRESSURE	4.0 MPa (40.8 Kg <sub>f</sub> /cm <sup>2</sup> )	
MIN. OPERATING PRESSURE	0.5 MPa ( 5 Kg <sub>f</sub> /cm <sup>2</sup> )	
MAX. PERMISSIBLE SPEED	6000 rpm	
WEIGHT	Kg	
MOMENT OF INERTIA(GD <sup>2</sup> )	Kg .m <sup>2</sup>	
TATAL LEAKAGE	1.0 L/min	
( 1 KN = 100 kgf , 1 MPa = 10 kgf/cm <sup>2</sup> )		

SCALE	PROJECTION	ITEM NO.	YASC-125
1:1		PART NAME	CLOSED HYDRAULIC CYLINDER CHECK VALVE TYPE
		PART NO.	2ASC12
서암기계공업주식회사 SEOAM MACHINERY INDUSTRY CO., LTD.			